



Gas Log Sets



BLACK FOREST OAK Model # SVMWO9
7 log set available in 20, 24" & 30" sizes.
Burns at 36,000 BTU maximum.



CHARRED BURNT OAK # SVFR10
7 log set available in 24" & 30" sizes.
Burns at 37,000 BTU maximum.

Sun Valley Vent Free Gas Log Sets provide a beautiful, authentic wood stack, dancing flames and glowing embers to warm your home with no outside venting required. For use in a solid burning fireplace and certain universal approved unvented fireplaces.

Both the **Charred Burnt Oak** and the **Black Forest Oak** are available with a manual or remote safety pilot system. No electricity is needed for reliable supplemental heat.

Enjoy money-saving fuel efficiency. Sets burn with the damper closed or opened. Sets include an Oxygen Depletion Sensor (ODS) for safe vent free operation and are design certified by C.S.A.

Distributed Exclusively by:

MASDA CORPORATION

Whippany, NJ	800-221-1425
Utica, NY	800-462-2606
Vineland, NJ	800-382-2631
East Haven, CT	203-469-7959
Haverhill, MA	800-446-2732
Richmond, VA	800-227-3439

SUN VALLEY VENT-FREE GAS LOG SET LIMITED WARRANTY

All Sun Valley Vent-Free Gas Logs are covered by a seven year (7) warranty.

All Sun Valley Vent-Free Burner component parts, except the ember bed, valves, pilots, and controls are covered by a three year (3) limited warranty.

All Sun Valley valves, pilot and controls are covered by a separate one (1) year limited warranty.





Burner Systems Series

CSA GLOWING COAL BURNER (SV9 SERIES)

For use with Black Forest Oak Log Sets (MWO-9 Series).



THE MINIMUM SIZE OF FIREPLACE FOR INSTALLATION OF THE SV9 VENT-FREE GAS LOG SET.

MODEL NO.	LOG SET SIZE	FIREPLACE SIZE			BTU RANGE <small>For Use with Propane Gas</small>
		WIDTH	DEPTH	HEIGHT	
SV9-20 SV9M-20	20"	24" front 20" rear (min)	11.5"	17"	17,000 – 36,000
SV9-24 SV9M-24	24"	29" front 20" rear (min)	11.5"	17"	17,000 – 36,000
SV9-30 SV9M-30	30"	34" front 26" rear (min)	11.5"	17"	17,000 – 36,000

Add a "P" to model number for L. P. gas.

CSA ADVANCED BURNER (SV10 SERIES)

For use with Charred Burnt Oak Log Sets (FR-10 Series).



THE MINIMUM SIZE OF FIREPLACE FOR INSTALLATION OF THE SV10 VENT-FREE GAS LOG SET.

MODEL NO.	LOG SET SIZE	FIREPLACE SIZE			BTU RANGE <small>For Use with Propane Gas</small>
		WIDTH	DEPTH	HEIGHT	
SV10-24 SV10M-24	24"	28" front 20" rear (min)	12" (min)	17"	19,000 – 37,000
SV10-30 SV10M-30	30"	34" front 20" rear (min)	12" (min)	17"	19,000 – 37,000

Add a "P" to model number for L. P. gas.

No.: L-F1-02002